

# E3/L3



APPLICATION:  
E3/L3

LEGACY MODEL:  
A2236

Code	Size	Ply	L.I.	Speed Rating	Rim in.	N.S. 32 <sup>nds</sup>	O.D. in.	S.W. in.	S.L.R. in.	R.C.	L.C.C. (1X) lbs.@psi	WT. lbs.
803033-74	15.5R25	**	160	B	12.00/1.3	35	50.0	15.9	22.4	154	9,900@76	331
803694-74	17.5R25	**	167	B	14.00/1.5	37	53.0	17.5	23.7	160	12,000@76	403
803696-74	20.5R25	**	177	B	17.00/2.5	40	58.7	20.5	26.1	177	16,100@76	600
803698-74	23.5R25	**	185	B	19.50/2.5	45	63.6	23.4	28.7	192	20,400@76	747
803700-74	26.5R25	**	193	B	22.00/3.0	50	69.3	26.5	31.2	209	25,400@76	946

RUBBER COMPOUND:

CUT RESISTANT	<input checked="" type="checkbox"/>
HEAT RESISTANT	<input checked="" type="checkbox"/>
STANDARD	<input type="checkbox"/>

The Aeolus AL36 features an aggressive tread design that delivers excellent traction while maintaining superior flotation characteristics. The enhanced rubber compound offers excellent wear and improved resistance to punctures. The AL36 is engineered to provide a stable, comfortable ride.

Features & Benefits:

- Cut & heat resistant compound
- Operator comfort
- Excellent flotation

Applications:

- Loader & dozer service

