

AL53

APPLICATION:
L5

LEGACY MODEL:
A2233

Code	Size	Ply	L.I.	Speed Rating	Rim in.	N.S. 32 ^{nds}	O.D. in.	S.W. in.	S.L.R. in.	R.C.	L.C.C. (1X) lbs.@psi	WT. lbs.
809694-74	17.5R25	**	182	A2	14.00/1.5	80	55.7	17.5	24.9	168	18700@94	644
809696-74	20.5R25	**	193	A2	17.00/2.5	90	61.9	20.5	28.0	187	25400@94	877
809698-74	23.5R25	**	201	A2	19.50/2.5	100	67.1	23.6	29.6	203	32000@94	1,151
809700-74	26.5R25	**	209	A2	22.00/3.0	120	71.1	26.6	32.2	215	40800@94	1,530
809702-74	29.5R25	**	216	A2	25.00/3.5	126	75.0	29.5	33.8	224	49400@94	2,020

RUBBER COMPOUND:

CUT RESISTANT	<input checked="" type="checkbox"/>
HEAT RESISTANT	<input type="checkbox"/>
STANDARD	<input type="checkbox"/>

The Aeolus AL53 is engineered for severe service applications such as mines, rock quarries, scrap and solid waste transfer stations. The AL53 features a cut and impact resistant compound and a bolstered sidewall to minimize tire damage and downtime. The AL53's tread design delivers exceptional traction and stability.

Features & Benefits:

- Cut & abrasion resistant compound
- Reinforced Sidewall
- Extra Deep Tread
- Exceptional Stability
- Excellent Tread Life

Applications:

- Graders
- Loaders

