



APPLICATION:
G2

LEGACY MODEL:
n/a

Code	Size	Ply	L.I.	Speed Rating	Rim in.	N.S. 32 ^{nds}	O.D. in.	S.W. in.	S.L.R. in.	R.C.	L.C.C. (1X) lbs.@psi	WT. lbs.
818420-74	1400R24	*	153	A8	8.00TG	33	54.1	14.2	24.4	163	8,050@54	377
818462-74	17.5R25	**	182	A2	14.00/1.5	37	55.7	17.5	25.3	171	1,8739@87	415
818472-74	20.5R25	**	193	A2	17.00/2.0	40	61.9	20.5	27.7	187	25,353@87	525
818481-74	23.5R25	**	201	A2	19.5/2.50	43	67.1	23.6	29.9	202	31,970@87	708

RUBBER COMPOUND:	
CUT RESISTANT	<input type="checkbox"/>
HEAT RESISTANT	<input type="checkbox"/>
STANDARD	<input checked="" type="checkbox"/>

The Aeolus ASnow radial is purpose built for use on graders and loaders where superior traction on snow and ice is essential. The ASnow features an aggressive, self-cleaning tread design that delivers exceptional traction in demanding winter/snow applications. The enhanced rubber compound offers excellent wear and improved resistance to punctures. The ASnow is engineered to provide a stable, comfortable ride while delivering excellent stability.

Features & Benefits:

- High traction – self-cleaning tread design
- Purpose built for winter/snow use
- Excellent flotation
- Wear and cut resistant tread compound

Applications:

- Graders
- Loaders
- Rigid dump trucks

