

# AGR20

APPLICATION:  
G2

LEGACY MODEL:  
A2230

| Code      | Size    | Ply | L.I. | Speed Rating | Rim in. | N.S. 32 <sup>nds</sup> | O.D. in. | S.W. in. | S.L.R. in. | R.C. | L.C.C. (1X) lbs.@psi | WT. lbs. |
|-----------|---------|-----|------|--------------|---------|------------------------|----------|----------|------------|------|----------------------|----------|
| 814420-74 | 1400R24 | **  | 153  | A8           | 8       | 32                     | 54.1     | 14.2     | 24.5       | 166  | 8,050@54             | 377      |

| RUBBER COMPOUND: |                                     |
|------------------|-------------------------------------|
| CUT RESISTANT    | <input checked="" type="checkbox"/> |
| HEAT RESISTANT   | <input type="checkbox"/>            |
| STANDARD         | <input type="checkbox"/>            |

The Aeolus AGR20 is engineered with an aggressive, self-cleaning tread design that provides excellent traction and flotation. The AGR20's wide-angled tread pattern delivers superior lateral stability.

#### Features & Benefits:

- Exceptional traction
- Wide-angled tread design for superior lateral grip
- Excellent flotation
- Superior durability and reduced cost per hour

#### Applications:

- Graders

