

IND4

AIN46

APPLICATION:
IND-4

LEGACY MODEL:
A2366

Code	Size	Ply	L.I.	Speed Rating	Rim in.	N.S. 32 ^{nds}	O.D. in.	S.W. in.	S.L.R. in.	R.C.	L.C.C. (1X) lbs.@psi	WT. lbs.
813421-74	1400R24	**	193	A5	10.00/1.5	60	55.9	15.0	24.3	161	25,400@145	485
813891-74	1600R25	***	200	A5	11.25/2.0	68	61.1	16.9	27.4	182	30,900@145	794
813893-74	1800R25	***	207	A5	13.00/2.5	81	65.9	19.8	30.6	203	38,600@145	970
813070-74	1800R33	***	214	A5	13.00/2.5	91	74.4	19.8	33.3	222	46,700@145	1,202

RUBBER COMPOUND:

CUT RESISTANT

HEAT RESISTANT

STANDARD



The Aeolus AIN46 is purpose built for use in port applications. It is engineered with an enhanced casing to deliver excellent stability and superior load carrying capacity. The AIN46 delivers a comfortable ride resulting in reduced operator fatigue.

Features & Benefits:

- Superior durability and reduced cost per hour
- Exceptional stability
- High speed capacity
- Wear and cut resistant tread compound

Applications:

- Industrial forklifts

