

E3/L3+

AL37

APPLICATION:
E3/L3+

LEGACY MODEL:
A2237

Code	Size	Ply	L.I.	Speed Rating	Rim in.	N.S. 32 ^{nds}	O.D. in.	S.W. in.	S.L.R. in.	R.C.	L.C.C. (1X) lbs.@psi	WT. lbs.
804698-74	23.5R25	**	185	B	19.50/2.5	50	64.1	23.6	28.9	194	20,400@76	805
804700-74	26.5R25	**	193	B	22.00/3.0	56	69.8	26.5	31.5	211	25,400@76	1,014
804702-74	29.5R25	**	200	B	25.00/3.5	60	73.7	29.4	32.3	223	30,900@76	1,204

RUBBER COMPOUND:

CUT RESISTANT	<input checked="" type="checkbox"/>
HEAT RESISTANT	<input checked="" type="checkbox"/>
STANDARD	<input type="checkbox"/>

The Aeolus AL37 is designed as a multi-purpose tire ideal for use on loaders, graders and earthmovers. It delivers exceptional traction and self-cleaning characteristics. The AL37's tread design provides superior flotation and stability. The AL37 features a reinforced sidewall design to reduce tire damage.

Features & Benefits:

- Cut & heat resistant compound
- Reinforced sidewall
- Deep tread
- Operator comfort
- Exceptional flotation

Applications:

- Loaders
- Graders

