



AL59

APPLICATION:
L5

LEGACY MODEL:
A2239

Code	Size	Ply	L.I.	Speed Rating	Rim in.	N.S. 32 ^{nds}	O.D. in.	S.W. in.	S.L.R. in.	R.C.	L.C.C. (1X) lbs.@psi	WT. lbs.
810696-74	20.5R25	**	193	A2	17.00/2.5	91	61.9	20.5	28.0	187	25400@94	736
810698-74	23.5R25	**	201	A2	19.50/2.5	98	67.1	23.6	29.6	203	32000@94	1,012
810700-74	26.5R25	**	209	A2	22.00/3.0	120	71.1	26.6	31.2	213	40800@94	1,380
810030-74	35X65R33	**	223	A2	28.00/3.5	123	81.9	35.3	36.9	245	60075@94	2,315

RUBBER COMPOUND:

CUT RESISTANT	<input checked="" type="checkbox"/>
HEAT RESISTANT	<input type="checkbox"/>
STANDARD	<input type="checkbox"/>

The Aeolus AL59 is engineered for use in severe service applications such as mines, rock quarries and solid waste stations. The AL59 features an aggressive tread design for superior grip and traction. The chip and cut resistant compound reduces flats and downtime. The AL59 has an extra deep tread for extended tread life.

Features & Benefits:

- High traction
- Cut & abrasion resistant compound
- Reinforced sidewall
- Extra Deep tread
- Excellent tread life
- Superior stability

Applications:

- Graders
- Loaders
- Rigid dump trucks

