

AR25

APPLICATION:
E2

LEGACY MODEL:
A2235

| Code | Size | Ply | L.I. | Speed Rating | Rim in. | N.S. 32 ^{nds} | O.D. in. | S.W. in. | S.L.R. in. | R.C. | L.C.C. (1X) lbs.@psi | WT. lbs. |
|-----------|---------|-----|------|--------------|-----------|------------------------|----------|----------|------------|------|----------------------|----------|
| 806900-74 | 1400R24 | *** | 170 | E | 10.00/1.5 | 29 | 53.9 | 15.0 | 24.3 | 161 | 11,681@100 | 397 |
| 806738-74 | 1400R25 | *** | 170 | E | 10.00/1.5 | 29 | 53.9 | 15.0 | 25.2 | 164 | 11,681@100 | 395 |
| 806891-74 | 1600R25 | *** | 179 | E | 11.25/2.0 | 37 | 59.1 | 16.9 | 26.6 | 176 | 17,100@131 | 639 |
| 806068-74 | 17.5R25 | *** | 170 | E | 14.00/1.5 | 37 | 53.0 | 17.5 | 23.7 | 160 | 13,200@70 | 430 |
| 806948-74 | 20.5R25 | *** | 179 | E | 17.00/2.5 | 40 | 58.7 | 20.5 | 26.4 | 175 | 17,100@100 | 606 |

RUBBER COMPOUND:

CUT RESISTANT

HEAT RESISTANT

STANDARD

The Aeolus AR25 is engineered specifically for use on mobile cranes and is DOT approved. The AR25 delivers exceptional stability, traction and a long tread life. The staggered tread block design provides superior water evacuation from the tread area for excellent traction. The AR25 features a cut and impact resistant compound and a bolstered sidewall to minimize tire damage and downtime.

Features & Benefits:

- DOT approved
- Cut & abrasion resistant compound
- Reinforced Sidewall
- Extra Deep Tread
- Exceptional Stability
- Excellent Tread Life

Applications:

- Mobile cranes

