

L5S

AS50

APPLICATION:
L5S

LEGACY MODEL:
A2200

| Code | Size | Ply | L.I. | Speed Rating | Rim in. | N.S. 32 ^{nds} | O.D. in. | S.W. in. | S.L.R. in. | R.C. | L.C.C. (1X) lbs.@psi | WT. lbs. |
|-----------|---------|-----|------|--------------|-----------|------------------------|----------|----------|------------|------|----------------------|----------|
| 811694-74 | 17.5R25 | ** | 182 | A2 | 14.00/1.5 | 81 | 55.7 | 17.5 | 25.3 | 171 | 18700@94 | 668 |
| 811698-74 | 23.5R25 | ** | 201 | A2 | 19.50/2.5 | 101 | 67.1 | 23.6 | 29.6 | 202 | 32000@94 | 1,182 |
| 811700-74 | 26.5R25 | ** | 209 | A2 | 22.00/3.0 | 120 | 71.1 | 26.6 | 31.1 | 213 | 40800@94 | 1,634 |
| 811702-74 | 29.5R25 | ** | 216 | A2 | 25.00/3.5 | 126 | 75.0 | 29.5 | 32.8 | 225 | 49400@94 | 2,072 |
| 811892-74 | 1800R25 | ** | 204 | A2 | 13.00/2.5 | 101 | 67.2 | 19.8 | 31.3 | 207 | 35300@120 | 1,202 |

| RUBBER COMPOUND: | |
|------------------|-------------------------------------|
| CUT RESISTANT | <input checked="" type="checkbox"/> |
| HEAT RESISTANT | <input type="checkbox"/> |
| STANDARD | <input type="checkbox"/> |

The Aeolus AS50 is engineered with an extra deep, smooth L5S tread design. The AS50 features wide shoulders and enhanced sidewall protection to ensure exceptional resistance to ruptures and tread damage. The enhanced rubber compound offers excellent wear and improved resistance to punctures.

Features & Benefits:

- Engineered for mining and waste handling operations
- Wear and cut resistant tread compound
- Superior reliability and tread life
- Excellent flotation
- Increased stability

Applications:

- Scrapers
- Loaders
- Mining

